

ACCESSORIES FOR RAISED FLOOR

TECHNICAL CHART PANEL TYPE



Steel Substructure Composed by :

Pedestal	<p>Head : in galvanized steel, with 4 spokes arranged to seat the stringers, included 4 holes drilled on the tabs for more safety with stringers (snap on).</p> <p>Tube : square pipe in high strength hot-dip galvanized steel , 18.5x1.2mm , with different heights and with notches on the adjustment nut on the tie-rod. For lengths over 298 mm , pipe dia 18.5x1.2mm is used.</p> <p>Base plate: in galvanized steel,dim. 100x100mm with 4 holes 8.5 mm for mechanical anchoring to the floor if required and with central flaring for adapting to not perfectly regular floor surfaces.</p>
Stringer	See the list at side.
Gasket	Thermoplastic material for an optimal stamping noise attenuation , from 2 mm thk.

Technical Data

pedestal height	Regulation range	Average weight with 600x600 mm grim			Maximum axial load EN12825
mm	mm	Kg/m²			KN
		M	H	E	
57	45/70	0.95	2.34	3.09	50
92	75/100	1.20	2.59	3.34	48
215	180/250	1.66	3.05	3.80	47
247	200/295	1.75	3.14	3.89	43.50
315	280/350	1.98	3.37	4.12	40
965	905/1.055	4.39	5.78	6.53	10

STRINGER KEY

M = medium stringer	30x30 mm
H = heavy stringer	25x25 mm
E = extra stringer	50x25 mm