

TECHNICAL CHARACTERISTICS

wineo Performance laminate flooring / Rock'n'Go wineo

Direct Pressure Laminate flooring acc. to EN 13329 for glueless installation

Format	1288 x 195 mm	
Product thickness	9 mm	
Panels / m² per box	8 / 2.01 m ²	
Boxes / m² per pallet	48 / 96.48 m ²	
Guarantee	25 years – Guarantee for private use according to Windmüller warranty conditions – www.wineo.de	

Classification			Product composition	
	Utilization class 23 EN ISO 10874	Heavy-duty use in the domestic area	1	Surface texture various embossings
	Utilization class 33 EN ISO 10874	Heavy-duty use in the commercial sector	2	Wear layer Melamine resin overlay
	Abrasion resistance EN 13329, annex E	AC5	3	Decor Decor paper
	Impact resistance EN 13329-2016, annex H	Small-diameter ball test ≥ 15 N Large-diameter ball test ≥ 1000 mm	4	Core board highly compressed core board
	Resistance to staining EN 438	Group 1 + 2: grade 5 Group 3: grade 4	5	Profile connection Fold-Down
	Light fastness EN ISO 105-B02	Light fastness (method 2) ≥ 6	6	Profile seal Aqua-Stop profile seal
	Residual indentation EN ISO 24343-1	Residual indentation ≤ 0.05 mm	7	Backing Melamine resin
	Effect of a furniture leg EN 424	Foot type 0 – no visible change	8	Layer Sound-Stop Layer with protective film
	Castor chair test EN 425	25000 revolutions no damage with rolls type W		Authentic joint design V4 – selected decors
	Thermal resistance EN 12667	0.06 (m ² K)/W		
	Impact sound reduction acc. ISO 717-2 Walking sound reduction – glued Walking sound reduction - not glued	17 dB 17.7 sone / 55.31 % 14.1 sone / 44.06 %		
	REACH	free from SVHC substances ≥ 0.1 %		
	Disposal	<u>Private:</u> like laminated furniture; possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170201		

Windmüller GmbH
Nord-West-Ring 21
D-32832 Augustdorf

DOP: 0101010
EN 14041:2004 / AC2006
1658

www.wineo.de

ÉMISSIONS DANS L'AIR INTÉRIEUR*

A+

A+
A
B
C

Information representative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (très faibles émissions)

- Relevant Information:**
- LA149SYSV4 / Dancing in the Dark = AC4 / NK 32
 - Walking noise reduction measured according to Windmüller works standard, Detmold site, based on EPLF WD 021029-5
 - Underfloor heating: In conjunction with suitable underlay material, suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperature of 27° C.
 - Cleaning and care: see separate cleaning & care instruction.
 - Technical subjects can be changed by Windmüller GmbH.